



STANDARD 8'-0" EXTENSION:

1. REMOVE ONE EXISTING END POST.
2. INSTALL NEW LINE POST AT PREVIOUS POST POSITION.
3. ATTACH NEW TOP RAIL AND MID RAIL TO LINE POST. HAND TIGHTEN SETSCREWS.
4. ATTACH EXISTING END POST TO TOP RAIL AND MID RAIL. HAND TIGHTEN SETSCREWS.
5. ANCHOR NEW POST POSITION. ANCHORS NOT PROVIDED.
6. USING A LEVEL, CHECK THAT POST ARE VERTICAL AND RAILS ARE LEVEL.
7. TIGHTEN ALL SETSCREWS.

THIS DRAWING AND ALL THE INFORMATION THEREON IS THE PROPERTY OF THE HOLLANDER MFG. CO., IS CONFIDENTIAL AND MUST NOT BE MADE PUBLIC, NOR COPIED, NOR USED, TO THE DISADVANTAGE OF SAID HOLLANDER MFG. CO. AND IS SUBJECT TO RETURN ON DEMAND.
 COPYRIGHT 2013.
 HOLLANDER - MANUFACTURING CO.

NO.	REVISIONS	DATE	APPROVED
0	RELEASED FOR APPROVAL	1-15-13	BW

Hollander[®]
 STRUCTURAL ENGINEERING GROUP
 10285 WAYNE AVENUE
 CINCINNATI, OH 45215-6399
 PHONE: (800) 772-8800 FAX: (502) 772-8806
 WWW.HOLLANDER.COM

PROJECT
 EXTENSION RAIL SECTION
 8'-0" c/c POST
 42" HIGH RAIL

CUSTOMER

DESCRIPTION
 BUMBLE BEE RAIL SECTION DRAWINGS

DESIGN BY: GG	APPROVED BY: BW	DATE: 1-15-12
PROJECT NO: 50341		SCALE: NTS
MATERIAL: POWDER COAT		PROJECT NO: 7055-S
STL. PIPE/ALUM FITTING		SHEET 1 OF 1

